

H3.2 vertical timber
batten
*See note
Wall underlay

NC226
Impervious barrier between
batten & cladding

NC204
10g ss pan head screws with
30mm min embedment

NC203E
Fixing bracket @ 600mm centers

Drained and vented cavity
as per E2/AS1

2x 2.8x50mm hot dipped galvanised
clout nails in to nog framing @ 600
centres. (SS for Exposure Zone D)
(2 nails per batten)

NC134P
Pre-slotted base channel.
Providing 2000mm² of ventilation
per linear meter

Cavity closer as per E2/AS1
(By others)

Cavity batten note:

- 20mm single castellated timber battens required for all Nu-Wall installations.
- Batten to have 15° slope for moisture egress
- Allow 6mm gap between vertical and horizontal battens
- Sill and head battens to be max. 500mm with a 6mm gap to each segment
- 18mm single castellated battens are available from Nu Wall for all vertical applications to wall junctions and jambs
- Proprietary Nu-Wall Alibat is available as an alternative when a structural non-combustable cavity batten is required



nu-wall
CLADDING

Nu-Wall cladding horizontal on cavity Typical base channel fixing

© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited

NW-HOC-005.02

Drawn by: Nu-Wall

Date: 02/07/2025

Checked by: RL, GT

Scale: 1:2 @ A4