



**NOTE 1**  
Rigid Air Barrier (RAB) also required in *Extra High* wind zones. Refer to E2/AS1 (section 9.1.7.2)

**NOTE 2**  
Detail depicts use of starter strip to locate a full board. Refer to NW-HOC-019 where a full board occurs

Stop-end tabbed up on both sides of head flashing

**General note:**

- Cladding fixings omitted for clarity

**Window setting out notes:**

- 17-18mm for hollow fin windows
- 18-20mm for solid fin windows

**Cavity batten note:**

- 20mm single castellated timber battens required for all Nu-Wall installations.
- Batten to have 15° slope for moisture egress
- Allow 6mm gap between vertical and horizontal battens
- Sill and head battens to be max. 500mm with a 6mm gap to each segment
- 18mm single castellated battens are available from Nu Wall for all vertical applications to wall junctions and jambs
- Proprietary Nu-Wall Alibat is available as an alternative when a structural non-combustable cavity batten is required

Interactive assembly  
instructions available  
<http://wksap.nz/nw-hoc-win2>



Get WORKINGSPEC from  
Apple App Store/Google Play



	Nu-Wall cladding horizontal on cavity		NW-HOC-018.02	
	Typical head section - notched using NC134P base channel		Drawn by: Nu-Wall	Date: 02/07/2025
	© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited		Checked by: RL, GT	Scale: 1:2 @ A4